

# Colliers de serrage



## Caractéristiques techniques

Références	Ø Intérieur Epaisseur du tuyau	Serrage		Dimensions		Boulons	Matière
		Minimum	Maximum	A	B		
RK019	19 * 6,0	30	33	63	50	M6 * 20	Aluminium
RKR019	19 * 6,0	30	33	63	50	M6 * 20	Inox
RK025	25 * 6,0	36	39	69	50	M6 * 20	Aluminium
RKR025	25 * 6,0	36	39	69	50	M6 * 20	Inox
RK032	32 * 6,0	43	46	76	50	M6 * 20	Aluminium
RKR032	32 * 6,0	43	46	76	50	M6 * 20	Inox
RK038	38 * 6,5	50	52	83	50	M6 * 20	Aluminium
RKR038	38 * 6,5	50	52	83	50	M6 * 20	Inox
RK050	50 * 8,0	64	67	102	56	M8 * 25	Aluminium
RKR050	50 * 8,0	64	67	102	56	M8 * 25	Inox
RK065	65 * 7,0	78	82	120	74	M8 * 25	Aluminium
RKR065	65 * 7,0	78	82	120	74	M8 * 25	Inox
RK075	75 * 8,0	89	93	132	76	M8 * 25	Aluminium
RKR075	75 * 8,0	89	93	132	76	M8 * 25	Inox
RK100	100 * 8,0	114	119	166	120	M12 * 40	Aluminium
RKR100	100 * 8,0	114	119	166	120	M12 * 40	Inox

La boulonnerie est livrée en acier carbone bichromaté avec les 1/2 coquilles en aluminium et en acier inox avec les 1/2 coquilles inox.  
Disponible sur stock jusqu'au DN100.